

## **B-LFP48-200PW**

Parallel capacity from 10.24 kWh to 327.68 kWh



The B-LFP48-200PW is a 51.2 volt, 10,24 kWh wall-mounted home battery for solar energy storage systems using the safest lithium ion chemical, lithium iron phosphate (LiFePo4), a flexible, scalable (up to 32 batteries can be used simultaneously to provide additional energy storage capacity) lithium battery storage solution designed for home solar power systems.



Modular and scalable



Max. 32 in parallel



Better price, bigger capacity



10-year warranty & technical support



30 days delivery period



For on-grid and off-grid



**UL Standard Battery Pack** 



High cycle life and deep cycle capability



Safe and reliable LiFePO4

## Specification

Item	General Parameter	
Model	B-LFP48-200PW	
Battery Type	LiFePO4	
Nominal Voltage (V)	51.2	
Nominal Capacity (wh)	10240	
Usable Capacity (wh)	9216	
Cell & Method	16S2P	
Dimension(mm)(W*H*D)	820*490*147	
Weight(Kg)	95	
Discharge Voltage (V)	47	
Charge Voltage (V)	55	
Charge	Rate. Current / Power	100A / 5.12kW
	Max. Current / Power	160A / 8.192kW
	Peak Current / Power	210A / 10.752kW
Discharging	Rate. Current / Power	200A / 10.24kW
	Max. Current / Power	220A / 11.264kW, 1s
	Peak Current / Power	250A / 12.80kW, 1s
Communication	RS232, RS485, CAN, WIFI(Optional), Bluetooth(Optional)	
Depth Of Discharge(%)	90%	
Expansion	up to 32 units in parallel	
Working Temperature	Charge	0~55°C
	Discharge	-20~55°C
Storage Temperature	0~35°C	
Short Circuit Current /Duration Time	350A, Delay time 500μs	
Cooling Type	Nature	
Protection Level	IP20	
Monthly Self-discharge	≤ 3%/month	
Humidity	≤ 60% ROH	
Altitude(m)	< 4000	
Warranty	10 Years	
Design Life	> 15 Years (25°C / 77°F)	
Cycle Life	> 6000 cycles, 25°C	
Certification & Safety Standard	UN38.3, UL1973, IEC62619, CEC	

Note: Customized models and adjusted parameters are available upon request.











Facebook

Linkedin

Tiktok

Instagram

Youtube